



Product Catalogue

TWC Series



About Us

Uniarc is part of a group of companies specializing in the production of Welding and Cutting torches.

With over 40 years experience, the group is positioned as a global leader at the heart of the welding torch industry.

Originally established in the United Kingdom in the 1980's, the company is now a fully-fledged, vertically integrated Chinese product innovator and manufacturer.

Our customers span a full cross section of the industry, ranging from general distribution to leading global original equipment manufacturers.

Our products are used in a broad cross-section of industrial sectors ranging from auto body repair to ship building.

Whether you need a standard off the shelf product or a customized branded option with your own colours, logos and packaging we have a one stop solution for your requirements.

Our team are here to help, contact us today if you need anymore information.



find out more www.uniarctorchology.com



Contents

Features Focus	4
Range Overview	5
Torch Model	
TW NO.2	6
TW NO.3	7
TW NO.4	8
TW NO.5	9
Wear Parts	
TWC Nozzles	10
TWC Contact Tips	12
TWC Diffusers	13
TWC Liners	14



TWC Mig / Mag Air-Cooled Series Features Focus



Swan Necks Manufactured to the same specification as the OEM.

Handles and Cable Supports Designed to combine balance, positioning and ergonomics with practical torch performance, cable life and consistent wire feed.

Air-Cooled Cable Systems Cable assemblies offer outstanding flexibility with the highest heat and abrasion resistance of any known cable.

Cable end and crimp systems ensure maximum conductivity whilst the outer jacket is constructed from cross-linked polymers providing a tear proof outer with a burn threshold of 375°C.

Rear Cable Support Extra length cable support systems ensure smooth and consistent wire feed at any angle.

Housings, Nuts and Supports

Tough and damage resistant, housings and nuts are formed in robust glass-reinforced polymers encasing all conductive parts in accordance with EN60974-7.

Consumable Parts

All wear and spare parts are manufactured to the same specification as the OEM and are fully interchangeable.

Hanger Hook

A "plug and play" option, they encourage the operator to hang the torch off the ground where it is easy to locate.

Knuckle Joint and Cable Support

Small movements of the handle and neck are possible independent of the cable assembly. A moulded polymer cable support increases flexibility and electrode support.



Terminations

A comprehensive range of USA and European style terminations ensures worldwide compatibility.




Euro Terminations Fitted with unbreakable spring loaded gun plug body pins.

TWC Mig / Mag Air-Cooled Series

Ratings: 150 Amp to 400 Amp, Mixed Gas M21






TW NO.2 Air-Cooled Mig Welding Torch



Rating: 200A CO2 150A mixed gas M21, EN60974-7 @ 60% duty cycle. 0.6 to 1.2mm / 0.023-0.045" wires

Euro Terminations




Description		Part Number		
		10ft / 3mt	12ft / 4mt	15ft / 5mt
	Welding Torch c/w Euro Fitting	U2-10E	U2-12E	U2-15E
	Welding Torch c/w Tweco Fitting	U2-10T	U2-12T	U2-15T

Spare part

	Part Number	Description		Part N
1	U32	Adjustable Nozzle Insulator	12	UC28
2	U62J60	Metal Jacket Swan Neck	13	UB15
3	U102	Block c/w Spacer & Screws	14	UXL1
4	U244T	Control Wire Terminals	15	SCSP
5	UB5044	Hose Clamp 18.5mm	16	SC25
6	U141-6S	Spring Cable Support Small & Ball Joint	17	UBL1
7	U200-10E	Cable Assembly x 10ft Euro	18	UC15
	U200-12E	Cable Assembly x 12ft Euro	19	UB15
	U200-15E	Cable Assembly x 15ft Euro	20	UC17
8	UP83	Handle With Hook & Screw	21	UB15
9	U92	Trigger Switch	22	UXL1
10	U152	Hanger Hook		
11	U122FMS	Screw Pack		

Description
Cable Support
Cable Terminal Male
Cable End Lock Nut (M12 x 1.0)
Gun Plug Housing Screw
Gun Plug Housing
Gun Plug Screw
Gun Plug Nut
Gun Plug Terminal Female
Gun Plug Body
Gun Plug 'O' Ring
Liner Retaining Nut

Torches are available with various terminations -please email info@uniarctorchology.com




TW NO.3 Air-Cooled Mig Welding Torch

Rating: 300A CO $_2$ 250A mixed gas M21, EN60974-7 @ 60% duty cycle. 0.8 to 1.6mm / 0.030-1/16" wires



Euro Terminations



_	Description	Part Number		
		10ft / 3mt	12ft / 4mt	15ft / 5mt
	Welding Torch c/w Euro Fitting	U3-10E	U3-12E	U3-15E
	Welding Torch c/w Tweco Fitting	U3-10T	U3-12T	U3-15T

Spare	parts
-------	-------

	Part Number	Description		Part Number	Description
1	U34A	Adjustable Nozzle Insulator	12	UC8026	Housing Spring
2	U63J60	Metal Jacket Swan Neck	13	UB1522	Cable Terminal Male
3	U102	Block c/w Spacer & Screws	14	UXL1542	Cable End Lock Nut (M12 x 1.0)
4	U244T	Control Wire Terminals	15	UT8028	Cable Support Nut
5	U132-12	Cable Hose Clamp	16	UT5022	Large Housing
6	UT8018S	Spring Cable Support Medium & Ball Joint	17	SC8017	Large Housing Wire Cover
7	U300-10E	Cable Assembly x 10ft Euro	18	UBL1541	Gun Plug Screw
	U300-12E	Cable Assembly x 12ft Euro	19	UB1519/S	Gun Plug Nut
	U300-15E	Cable Assembly x 15ft Euro	20	UB1523	Gun Plug Terminal Female
8	UP83	Handle With Hook & Screw	21	UC174EX-1	Gun Plug Body
9	U92	Trigger Switch	22	UB1524	Gun Plug 'O' Ring
10	U152	Hanger Hook	23	UXL1826	Liner Retaining Nut
11	U122FMS	Screw Pack			

Torches are available with various terminations -please email info@uniarctorchology.com

All products conform to EN60974-7, **(** and are RoHS2, REACH and WEEE compliant

A Martin


TW NO.4 Air-Cooled Mig Welding Torch



Rating: 400A CO₂ 350A mixed gas, M21 EN60974-7 @ 60% duty cycle. 0.8 to 2.0mm / 0.030-5/64" wires



A MARK





Description	Part Number	Part Number		
	10ft / 3mt	12ft / 4mt	15ft / 5mt	
Welding Torch c/w Euro Fitting	U4-10E	U4-12E	U4-15E	
Welding Torch c/w Tweco Fitting	U4-10T	U4-12T	U4-15T	

Spar	е	parts

	Part Number	Description		Part Number	Description
1	U34A	Adjustable Nozzle Insulator	12	UC8026	Housing Spring
2	U64J60	Metal Jacket Swan Neck	13	UB1522	Cable Terminal Male
3	U104	Connection Block c/w Spacer	14	UXL1542	Cable End Lock Nut (M12 X 1.0)
4	U244T	Control Wire Terminals	15	UT8028	Cable Support Nut
5	U132-12	Cable Hose Clamp	16	UT5022	Large Housing
6	UBE8018	Spring Cable Support & Ball Joint	17	SC8017	Large Housing Wire Cover
7	U400-10E	Cable Assembly x 10ft Euro	18	UBL1541	Gun Plug Screw
	U400-12E	Cable Assembly x 12ft Euro	19	UB1519/S	Gun Plug Nut
	U400-15E	Cable Assembly x 15ft Euro	20	UB1523	Gun Plug Terminal Female
8	UP84A	Handle With Hook & Screw	21	UC174EX-1	Gun Plug Body
9	U94R	Trigger Switch	22	UB1524	Gun Plug 'O' Ring
10	U154	Hanger Hook	23	UXL1826	Liner Retaining Nut
11	U124FMS	Screw Pack			

Torches are available with various terminations -please email info@uniarctorchology.com





	10ft / 3mt	12ft / 4mt	15ft / 5mt
Welding Torch c/w Euro Fitting	U5-10E	U5-12E	U5-15E
Welding Torch c/w Tweco Fitting	U5-10T	U5-12T	U5-15T

	Spare part	
	Part Number	Description
1	U65J60	Metal Jacket Swan Neck
2	U104	Connection Block c/w Spacer
3	U244T	Control Wire Terminals
4	U134-14	Cable Hose Clamp
5	UBE8018	Spring Cable Support & Ball Joint
6	U500-10E	Cable Assembly x 10ft Euro
	U500-12E	Cable Assembly x 12ft Euro
	U500-15E	Cable Assembly x 15ft Euro
7	UP85	Handle With Hook & Screw
8	U94R	Trigger Switch
9	U154	Hanger Hook
10	U124FMS	Screw Pack
11	UC8026	Housing Spring
12	UB1522	Cable Terminal Male
13	UXL1542	Cable End Lock Nut (M12 x 1.0)
14	UT8028	Cable Support Nut

Part Number 15 UT5022 Large Housing 16 SC8017 Large Housing Wire Cover 17 UB1526 Gun Plug Screw UB1519/S Gun Plug Nut 18 UB1523 Gun Plug Terminal Female 19 20 U174EX-1 Gun Plug Body Gun Plug 'O' Ring UB1524 21 22 UXL1826 Liner Retaining Nut

Torches are available with various terminations -please email info@uniarctorchology.com

All products conform to EN60974-7, **CE** and are RoHS2, REACH and WEEE compliant

©All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted by any means, electronic, mechanical, photocopying or otherwise without the prior permission of ©Uniarc® the copyright holder.






TWC	Nozzles


Part No. Descri

Bore Length Wall Material


U21-37	Nozzle Self Insulated	9.5	56.5mm	1.6mm	Copper	•		
U21-50	Nozzle Self Insulated	12.7	56.5mm	1.6mm	Copper	•		•
U21-62	Nozzle Self Insulated	15.9	52.5mm	1.6mm	Copper	٠		



U22-50	Nozzle Adjustable	12.8	78mm	1.25mm	Copper	•		
U22-62	Nozzle Adjustable	16.0	78mm	1.25mm	Copper	٠		•



U24CT-50S	Nozzle Fixed Coarse Thread	12.8	44.5mm	1.95mm	Copper		•	
U24CT-62S	Nozzle Fixed Coarse Thread	16.0	44.5mm	1.90mm	Copper		•	
U24CT-75S	Nozzle Fixed Coarse Thread	19.0	44.5mm	2.45mm	Copper			
U34CT	Nozzle Insulator Coarse Thread		49.5mm			•	•	



U23-50	Nozzle Self Insulated	12.7	82mm	1.60mm	Copper	•	•	•
U23-62	Nozzle Self Insulated	15.9	82mm	1.60mm	Copper	•	•	•
U23-75	Nozzle Self Insulated	19.0	82mm	1.60mm	Copper	•	•	•


Standard wear part range

Torch package standard wear part set-up



TWC Nozzles


Bore Length Wall Material 🛱



27 A							-			
+ '	U24A-50	Nozzle Adjustable	12.8	88mm	1.25mm	Copper				
	U24A-62	Nozzle Adjustable	16.0	88mm	1.25mm	Copper		•	•	
t	U24A-75	Nozzle Adjustable	19.0	88mm	1.25mm	Copper			•	



U24AH-50	Nozzle Heavy Duty	12.8	2.25mm	Copper		٠	
U24AH-62	Nozzle Heavy Duty	16.0	2.25mm	Copper			
U24AH-75	Nozzle Heavy Duty	19.0	2.25mm	Copper		•	





U25CT-50	Nozzle Fixed Coarse Thread	12.8	56mm	1.6mm	Copper			•
U25CT-62	Nozzle Fixed Coarse Thread	16.0	56mm	1.95mm	Copper			•
U25CT-75	Nozzle Fixed Coarse Thread	19.0	56mm	2.45mm	Copper			•
U35CT	Nozzle Insulator Coarse Thread				Copper			•


• Standard wear part range • Torch package standard wear part set-up















TWC Co	intact Ti	DS		0.1	0.2	0.3	0.4	0.5
Part No.	Description	Material	Wire Size mm-INCH	M/	N N	_w_∧	_ ∧	N ML
U11-23	Contact Tip	Ecu	0.6-0.023"	•		•		•
U11-30	Contact Tip	Ecu	0.8-0.030"	•				•
U11-35	Contact Tip	Ecu	0.9-0.035"					•
U11-40	Contact Tip	Ecu	1.0-0.040"	•				•
U11-45	Contact Tip	Ecu	1.2-0.045"	•	•	•	•	•
U14-23	Contact Tip	Ecu	0.6-0.023"	•	•	•	•	•
U14-30	Contact Tip	Ecu	0.8-0.030"	•	•	•	•	•
U14-35	Contact Tip	Ecu	0.9-0.035"		•	•	•	•
U14-40	Contact Tip	Ecu	1.0-0.040"	•	•	•	•	•
U14-45	Contact Tip	Ecu	1.2-0.045"	•	•	•	•	•
U14-52	Contact Tip	Ecu	1.3-0.052"		•	•	•	•
U14-116	Contact Tip	Ecu	1.6-0.063"	•	•	•	•	•
U14-564	Contact Tip	Ecu	2.0-0.063"	•	•	•	•	•
U14H-30	Contact Tip	Ecu	0.8-0.030"		•	•	•	
U14H-35	Contact Tip	Ecu	0.9-0.035"		•	•	•	•
U14H-40	Contact Tip	Ecu	1.0-0.040"	•	•	•	•	•
U14H-45	Contact Tip	Ecu	1.2-0.045"	•	•	•	•	•
U14H-52	Contact Tip	Ecu	1.3-0.052"	•	•	•	•	•
U14H-116	Contact Tip	Ecu	1.6-1/16"	•	•	•	•	•
U14H-564	Contact Tip	Ecu	2.0-5/64"	•	•	•	•	•
U15HFC-40	Contact Tip	Ecu	1.0-0.040"	•		•		•
U15HFC-45	Contact Tip	Ecu	1.2-0.045"					•
U15HFC-52	Contact Tip	Ecu	1.3-0.052"	•				•
U15HFC-116	Contact Tip	Ecu	1.6-1/16"	•				•
U15HFC-332	Contact Tip	Ecu	2.4-3/32"	•				•
U15HFC-564	Contact Tip	Ecu	2.0-5/64"	•				•
			_					
U15H-30	Contact Tip	Ecu	0.8-0.030"	•				•
U15H-35	Contact Tip	Ecu	0.9-0.035"	•				•
U15H-40	Contact Tip	Ecu	1.0-0.040"	•				•
U15H-45	Contact Tip	Ecu	1.2-0.045"	•				•
U15H-52	Contact Tip	Ecu	1.3-0.052"	•				•
U15H-116	Contact Tip	Ecu	1.6-1/16"	•				•
U15H-332	Contact Tip	Ecu	2.4-3/32"					•
U15H-564	Contact Tip	Ecu	2.0-5/64"	•	•	•	•	•

Standard wear part range


Torch package standard wear part set-up





TWC Diffuser

U51	Gas Diffuser	Brass	•		•



U52	Gas Diffuser	Brass	•	•	•	•	
		•					



U52FN Gas Diffuser For CT/FN Nozzle Brass	•	٠			•	
---	---	---	--	--	---	--



U54A	Gas Diffuser	Brass		٠	٠	



Rel U55 Gas Diffuser ØA 3.5 ØB 6.0 Copper	• •
U55H Gas Diffuser ØA 4.0 ØB 7.0 Copper	• •
T U55SW Gas Diffuser ØA 3.5 ØB 5.0 Copper	• •



TWC Li				Wire Size	N NC	TW NO.2	N NC	N N
Part No.	Length	Description	Nipple	mm-INCH	F	F	F	F
		a e de cara e e comercia en esta comercia en entre de entre de entre de entre de entre de la defensione de la d	a la nava ka na ka		0000000	000000000000000000000000000000000000000	000000000000000000000000000000000000000	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
U42-3035-15	4.90mt	Steel Liner x 15ft	Moulded Nipple		٠	•		
U42-3035-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	0.8-0.9/0.030-0.035"	•	•	•	
	والمراجع والمحمو والمراجع				0000000	00000000000	000000000000000000000000000000000000000	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
UA42-3035-15	4.90mt	Steel Liner x 15ft	Brass Nipple	0.8-0.9/0.030-0.035"	•	•	•	•
UA42-3035-25	8.10mt	Steel Liner x 25ft	Brass Nipple	0.8-0.9/0.030-0.035"	•	•		
				· ·				
							-	
U42-4045-15 U42-4045-25	4.90mt	Steel Liner x 15ft	Moulded Nipple	1.0-1.2/0.040-0.045" 1.0-1.2/0.040-0.045"	•	•	•	•
042-4045-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	1.0-1.2/0.040-0.045	•	•	•	•
							,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
UA42-4045-15	4.90mt	Steel Liner x 15ft	Brass Nipple	1.0-1.2/0.040-0.045"	•	•	•	
UA42-4045-25	8.10mt	Steel Liner x 25ft	Brass Nipple	1.0-1.2/0.040-0.045"	•			

U42N-4045-15	4.90mt	Polyamide Liner x 15ft	Brass Nipple	1.0-1.2/0.040-0.045"	•	٠	•	٠	٠
U42N-4045-25	8.10mt	Polyamide Liner x 25ft	Brass Nipple	1.0-1.2/0.040-0.045"	٠	•	•	٠	٠

U44-3545-15	4.90mt	Steel Liner x 15ft	Moulded Nipple	0.9-1.2/0.035-0.045"		•	•	•
U44-3545-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	0.9-1.2/0.035-0.045"		٠	٠	•

					000000	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	000000000	000000000	000000
UA44-3545-15	4.90mt	Steel Liner x 15ft	Brass Nipple	0.9-1.2/0.035-0.045"			•	٠	•
UA44-3545-25	8.10mt	Steel Liner x 25ft	Brass Nipple	0.9-1.2/0.035-0.045"			•	٠	٠

• Standard wear part range • Torch package standard wear part set-up

11



Part No.	NEIS Length	Description	Nipple	Wire Size mm-INCH	TW NO.1	TW NO.2	TW NO.3	TW NO.4	TW NO.5
					nnnnn		000000000000000000000000000000000000000		100000
U44-116-15 U44-116-25	4.90mt 8.10mt	Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Moulded Nipple	1.6-1/16" 1.6-1/16"	•	•	•	•	•
									00000000
UA44-116-15 UA44-116-25	4.90mt 8.10mt	Steel Liner x 15ft Steel Liner x 25ft	Brass Nipple Brass Nipple	1.6-1/16" 1.6-1/16"	•	•	•	•	•
U44N-116-15	4.90mt	Polyamide Liner x 15ft	Brass Nipple	1.6-1/16"	•	•	•	•	•
U44N-116-25	8.10mt	Polyamide Liner x 25ft	Brass Nipple	1.6-1/16"		•	•	•	•
	_								
U44-564-15	4.90mt	Steel Liner x 15ft	Moulded Nipple	2.0-5/64"	•	•	•	•	•
U44-564-15 U44-564-25	4.90mt 8.10mt	Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Moulded Nipple	2.0-5/64" 2.0-5/64"	•	•	•	•	•
				-					•
				-					•
U44-564-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	2.0-5/64"	•	•	•	•	•
			Moulded Nipple	-					
U44-564-25	8.10mt	Steel Liner x 25ft Steel Liner x 15ft	Moulded Nipple	2.0-5/64" 2.0-5/64"	•	•	•	•	
U44-564-25	8.10mt	Steel Liner x 25ft Steel Liner x 15ft	Moulded Nipple	2.0-5/64" 2.0-5/64"		•	•	•	•
U44-564-25	8.10mt	Steel Liner x 25ft Steel Liner x 15ft	Moulded Nipple	2.0-5/64" 2.0-5/64"		•	•	•	•
U44-564-25	8.10mt	Steel Liner x 25ft Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Brass Nipple Brass Nipple	2.0-5/64" 2.0-5/64"		•	•	•	•
U44-564-25 UA44-564-15 UA44-564-25	8.10mt 4.90mt 8.10mt	Steel Liner x 25ft Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Brass Nipple Brass Nipple Moulded Nipple	2.0-5/64" 2.0-5/64" 2.0-5/64"		•	•	•	•
U44-564-25 UA44-564-15 UA44-564-25	8.10mt 4.90mt 8.10mt 4.90mt	Steel Liner x 25ft Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Brass Nipple Brass Nipple Moulded Nipple	2.0-5/64" 2.0-5/64" 2.0-5/64" 0.9-1.2/0.035-0.045"		•	•	•	•
U44-564-25 UA44-564-15 UA44-564-25	8.10mt 4.90mt 8.10mt 4.90mt	Steel Liner x 25ft Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Brass Nipple Brass Nipple Moulded Nipple	2.0-5/64" 2.0-5/64" 2.0-5/64" 0.9-1.2/0.035-0.045"				•	
U44-564-25 UA44-564-15 UA44-564-25	8.10mt 4.90mt 8.10mt 4.90mt	Steel Liner x 25ft Steel Liner x 15ft Steel Liner x 25ft	Moulded Nipple Brass Nipple Brass Nipple Moulded Nipple Moulded Nipple	2.0-5/64" 2.0-5/64" 2.0-5/64" 0.9-1.2/0.035-0.045"				•	

Standard wear part range
 Torch package standard wear part set-up



TWC Li Part No.	NE15 Length	Description	Nipple	Wire Size mm-INCH	TW NO.1	TW NO.2	TW NO.3	TW NO.4	TW NO.5
					nnnn			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	600000000
U45-116-15	4.90mt	Steel Liner x 15ft	Moulded Nipple	1.6-1/16"					

UA45-116-15	4.90mt	Steel Liner x 15ft	Brass Nipple	1.6-1/16"			•
UA45-116-25	8.10mt	Steel Liner x 25ft	Brass Nipple	1.6-1/16"			•

U45-564-15	4.90mt	Steel Liner x 15ft	Moulded Nipple	2.0-5/64"			•
U45-564-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	2.0-5/64"			•

-	-	
	_	
_	_	
-		

UA45-564-15	4.90mt	Steel Liner x 15ft	Brass Nipple	2.0-5/64"			•
UA45-564-25	8.10mt	Steel Liner x 25ft	Brass Nipple	2.0-5/64"			٠

				1000	0000000000	000000000	00000000000	AUUUUUU	
E 222 4 E	4 00 1	0 11: 150	2 4 2/22"						

U45-332-15	4.90mt	Steel Liner x 15ft	Moulded Nipple	2.4-3/32"			•
U45-332-25	8.10mt	Steel Liner x 25ft	Moulded Nipple	2.4-3/32"	•	•	•

						*****	******	///////////////////////////////////////	
UA45-332-15	4.90mt	Steel Liner x 15ft	Brass Nipple	2.4-3/32"				٠	_
UA45-332-25	8.10mt	Steel Liner x 25ft	Brass Nipple	2.4-3/32"					

Standard wear part range
 Torch package standard wear part set-up





Welding & Cutting Torch Technology

JINAN UNIARC WELDING TECHNOLOGY CO., LTD

13A Zhangjin Comprehensive Bonded Zone 33688, Jing Shi Dong Road Jinan Area of China (Shandong) Pilot Free Trade Zone Jinan 250102, P.R. China

> Tel: +86 531 88239823 Website: www.uniarctorchology.com Email: info@uniarctorchology.com MPU032 / V.2022.08